

Torque Wrench Set | 6.3 mm (1/4"), 10 mm (3/8"), 12.5 mm (1/2") | 31 pcs.



Product number: 74305

Weight: 6.05 kg

EAN: 4048769081379

- universal set composition
- suitable for tightening to torque for screwed connections with right-hand thread
- integrated reversible ratchet with narrow head shape
- ratchet mechanism, reversible
- easy locking and unlocking at the handle
- optimally designed aluminum handle for easy setting of the desired torque value, as well as a secure grip of the tool handle
- clearly audible release tone
- for tire changing on most popular wheel rims
- colour coded protective impact sockets suitable for manual and impact wrench operation

scope of delivery:

- 1 torque wrench | 6.3 mm (1/4") | 5 - 25 nm (BGS 2825)
- 1 torque wrench | 10 mm (3/8") | 10 - 60 nm
- 1 torque wrench | 12.5 mm (1/2") | 40 - 220 nm (BGS 2827)
- 1 spark plug socket, hexagon | 10 mm (3/8") drive | 14 mm (BGS 2400)
- 1 spark plug socket, hexagon | 12.5 mm (1/2") drive | 16 mm (BGS 2401)
- 1 spark plug socket, hexagon | 12.5 mm (1/2") drive | 18 mm (BGS 2402)
- 1 spark plug socket, hexagon | 12.5 mm (1/2") drive | 21 mm (BGS 2403)
- 1 "wobble" extension bar | 12.5 mm (1/2") | 125 mm (BGS 234)
- 1 "wobble" extension bar | 10 mm (3/8") | 75 mm (BGS 242)
- 1 digital tyre pressure gauge & tyre depth gauge | "2-in-1" (BGS 6647)
- 1 protective impact socket | 12.5 mm (1/2") drive | 17 mm (BGS 7201)
- 1 protective impact socket | 12.5 mm (1/2") drive | 19 mm (BGS 7202)
- 1 protective impact socket | 12.5 mm (1/2") drive | 21 mm (BGS 7203)
- 1 protective impact socket | 12.5 mm (1/2") drive | 22 mm (BGS 7208)
- 1 bit socket | 6.3 mm (1/4") drive | cross slot PH1 (BGS 2487)
- 1 bit socket | 6.3 mm (1/4") drive | cross slot PH2 (BGS 2488)
- 1 bit socket | 6.3 mm (1/4") drive | cross slot PH3 (BGS 2489)
- 1 bit socket | 6.3 mm (1/4") drive | T-Star (for Torx) T10 (BGS 2590)
- 1 bit socket | 6.3 mm (1/4") drive | T-Star (for Torx) T15 (BGS 2591)
- 1 bit socket | 6.3 mm (1/4") drive | T-Star (for Torx) T20 (BGS 2592)
- 1 bit socket | 6.3 mm (1/4") drive | T-Star (for Torx) T25 (BGS 2593)
- 1 bit socket | 6.3 mm (1/4") drive | T-Star (for Torx) T30 (BGS 2595)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 2 mm (BGS 5153)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 2.5 mm (BGS 5154)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 3 mm (BGS 2497)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 4 mm (BGS 2498)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 5 mm (BGS 2499)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 6 mm (BGS 2500)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 8 mm (BGS 2502)
- 1 bit socket | 6.3 mm (1/4") drive | internal hexagon 10 mm (BGS 2161-10)
- 1 wire brush with plastic handle | brass