

## VDE Pliers, Screwdriver and Socket Set | BGS systainer® | 36-pcs.



Product number: 70230

Weight: 5.745 kg EAN: 4048769085285

- perfect tool combination for use in the range of electrical installations or for repair and maintenance work on hybrid and electric vehicles
- equipped with insulated tools and tested according to DIN EN/IEC 60900
- VDE insulated up to 1000 V
- intelligent transport and storage system
- one-handed operation: close, open and connect to other systainers
- made of stable ABS plastic
- functional handle and T-Loc closure
- this case is part of a multi-component system, stackable (containers can be locked to another and carried)
- protective padding in the upper lid
- inside dimensions: width 383 mm | height 127.5 mm | depth 267 mm
- splash-proof
- tool trays made from high-resistance foam
- the tools are protected in the hard foam tray and are stowed in the recesses in a non-slip manner
- each individual tool has its appropriate place

• material: chrome vanadium steel

## scope of delivery:

- 1 VDE Screwdriver | slot SL 3 mm | blade length 75 mm (BGS 4925)
- 1 VDE Screwdriver | slot SL 4 mm | blade length 100 mm (BGS 4924)
- 1 VDE Screwdriver | slot SL 5.5 mm | blade length 125 mm (BGS 4940)
- 1 VDE Screwdriver | slot SL 6.5 mm | blade length 150 mm (BGS 4941)
- 1 VDE Screwdriver | cross slot PH0 | blade length 75 mm (BGS 4942)
- 1 VDE Screwdriver | cross slot PH1 | blade length 80 mm (BGS 4926)
- 1 VDE Screwdriver | cross slot PH2 | blade length 100 mm (BGS 4927)
- 1 voltage tester | 120 250 V | 140 mm (BGS 725)
- 1 VDE wire stripping pliers | 160 mm (BGS 7156)
- 1 VDE long nose pliers | 160 mm (BGS 7151)
- 1 VDE long nose pliers | 200 mm (BGS 7152)
- 1 VDE long nose pliers | angular | 200 mm (BGS 7153)
- 1 VDE side cutter | 160 mm (BGS 7154)
- 1 VDE reversible ratchet | fine tooth | 10 mm (3/8") | 1000 V, with quick release, no. of teeth in ratchet head: 72, length: 200 mm (BGS 701)
- 1 VDE socket, hexagon 6 mm, length: 72 mm
- 1 VDE socket, hexagon 7 mm, length: 72 mm
- 1 VDE socket, hexagon 8 mm, length: 72 mm
- 1 VDE socket, hexagon 9 mm, length: 72 mm
- 1 VDE socket, hexagon 10 mm, length: 72 mm
- 1 VDE socket, hexagon 11 mm, length: 72 mm
- 1 VDE socket, hexagon 12 mm, length: 72 mm
- 1 VDE socket, hexagon 13 mm, length: 72 mm
- 1 VDE socket, hexagon 14 mm, length: 72 mm
- 1 VDE socket, hexagon 15 mm, length: 72 mm
- 1 VDE socket, hexagon 16 mm, length: 72 mm
- 1 VDE socket, hexagon 17 mm, length: 72 mm
- 1 VDE socket, hexagon 18 mm, length: 72 mm
- 1 VDE socket, hexagon 19 mm, length: 72 mm
- 1 VDE socket, hexagon 20 mm, length: 72 mm
- 1 VDE socket, hexagon 21 mm, length: 72 mm
- 1 VDE socket, hexagon 22 mm, length: 72 mm
- 1 VDE extension bar, length: 100 mm
- 1 VDE extension bar, length: 250 mm
- 1 VDE bit socket, 10 mm (3/8") drive | spline (for XZN) M8, length: 67 mm
- 1 VDE bit socket, 10 mm (3/8") drive | spline (for XZN) M10, length: 67 mm
- 1 VDE bit socket, 10 mm (3/8") drive | spline (for XZN) M12, length: 67 mm