



Socket Set | 6.3 mm (1/4") / 12.5 mm (1/2") Drive | 174 pcs.



Product number: 9191

Weight: 5.64 kg

EAN: 4026947091914

2 sockets sets

1. socket set, 6.3 mm (1/4"), 130 pcs.

- reversible ratchet, finely toothed, 72 teeth with quick release function
- extension bar 50 mm
- sliding handle
- spinner handle, 150 mm
- sockets, 4 - 4.5 - 5 - 5.5 - 6 - 7 - 8 - 9 - 10 - 11 - 12 - 13 - 14 mm
- bit adaptor

- bits:
 - cross slot, length 50 mm: PZ1 - PZ2
 - slot sl, length 50 mm: 4 - 6 mm
 - wing nut bit
 - internal hexagon non-tamperproof, inch sizes: 1/16" - 5/64" - 3/32" - 7/64" - 1/8" - 9/64" - 5/32" - 3/16" - 7/32" - 1/4"
 - internal hexagon tamperproof, inch sizes: 5/64" - 3/32" - 7/64" - 1/8" - 9/64" - 5/62"
 - internal hexagon non-tamperproof, metric: 1.5 - 2 - 2.5 - 3 - 4 - 5 - 5.5 - 6 - 8 mm
 - internal hexagon tamperproof, metric: 2 - 2.5 - 3 - 4 - 5 - 6 mm
 - 2-pin: 4 - 6 - 8 - 10 mm
 - T-Star non-tamperproof (for Torx): T8 - T10 - T15 - T20 - T25 - T27 - T30 - T35 - T40
 - T-Star tamperproof (for Torx): T8 - T10 - T15 - T20 - T25 - T27 - T30 - T35 - T40
 - spline (for XZN): M5 - M6 - M8
 - 4-point: S0 - S1 - S2 - S3
 - cross slot: PZ0 - PZ0 - PZ1 - PZ1 - PZ2 - PZ2 - PZ2 - PZ2 - PZ3 - PZ3
 - cross slot: PH0 - PH0 - PH1 - PH1 - PH2 - PH2 - PH2 - PH2 - PH3 - PH3
 - slot sl: 3 - 4 - 4.5 - 5 - 5.5 - 6 - 6.5 - 7 - 8 mm
 - 2-panel: C1 - C2 - C3
 - 3-panel: 1 - 2 - 3 - 4 - 6 - 8 - 10
- L-type wrenches, internal hexagon: 1 - 1.5 - 2 - 2.5 - 3 - 4 - 5 mm

2. socket set, 12.5 mm (1/2"), 44 pcs.

- reversible ratchet, finely toothed, 72 teeth with quick release function
- extension bar, 125 mm and 200 mm
- sliding handle adaptor, for extension bar
- joint
- sockets, hexagon, 10 - 11 - 12 - 13 - 14 - 15 - 16 - 17 - 18 - 19 - 20 - 21 - 22 - 24 - 27 - 30 - 32 mm
- bit adaptor for 8 mm (5/16") bits
- bits, 8 mm (5/16") drive:
 - cross slot: PH3 - PH4 / PZ3 - PZ4
 - slot sl: 8 - 10 - 12 mm
 - T-Star non-tamperproof (for Torx): T40 - T45 - T50 - T55 - T60
 - T-Star tamperproof (for Torx): T40 - T45 - T50 - T55 - T60
 - spline (for XZN): M8 - M10 - M12
 - internal hexagon: 7 - 8 - 10 - 12 mm